




	<b>Aims 400</b>	<b>Voltec 400</b>	<b>Rally 400</b>	<b>Cobra 400</b>	<b>B &amp; D 400</b>
<b>Manufacturer:</b>	Aims 400	Voltec 400	Rally 400	Cobra 400	B & D 400
<b>Model:</b>	PWRINV400R	10-00477	7392	CPI-480	PI400AB
<b>DC Input:</b>	12 Volt	12 Volt	12 Volt	12 Volt	12 Volt
<b>Continuous Power:</b>	400 Watts	400 Watts	400 Watts	400 Watts	400 Watts
<b>Surge Power:</b>	800 Watts	800 Watts	800 Watts	800 Watts	800 Watts
<b>Receptacles:</b>	2	2	2	2	2
<b>USB Port:</b>	No	Yes	Yes	Yes	Yes
<b>Bonus Port:</b>	No	No	<b>iPod Quick Charge</b>	No	No
<b>Cooling Fan:</b>	Thermal	Thermal	Thermal	Yes	Thermal
<b>Enclosed Cables:</b>	Cig & Direct	Cig & Direct	Cig & Direct	Cig & Direct	Cig & Direct
<b>Operating Voltage:</b>	10 to 15 Volts	10 to 15 Volts	10.5 to 15 Volts	10.4 to 14.4 Volts	10.5 to 15 Volts
<b>Output Voltage:</b>	120 Volts AC	120 Volts AC	120 Volts AC	120 Volts AC	120 Volts AC
<b>Output Wave Form:</b>	Modified	Modified	Modified	Modified	Modified
<b>Output Frequency:</b>	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz
<b>Over Temp Protection:</b>	Yes	Yes	Yes	Yes	Yes
<b>Over Load Protection:</b>	Yes	Yes	Yes	Yes	Yes
<b>Low Voltage Alarm:</b>	10.5 +/-0.5 Volts	10.2 – 10.8 Volt	< 11.5 Volt DC	10.2 – 10.8 Volt DC	< 11.5 Volt DC
<b>Low Voltage Shutdown:</b>	10.0+/-0.5 Volts	9.2 – 9.8 Volt	< 10.5 Volt DC	9.2 – 9.8 Volt DC	< 10.5 Volt DC
<b>No Load Current:</b>	< 0.75 Amps	< 0.3A	< 0.45 Amps	< 0.5 Amps	< 0.6 Amps
<b>Full Load Efficiency:</b>	85%	85%	80%	83%	83%
<b>1/3 Load Efficiency:</b>	90%	90%	82%	88%	88%
<b>Dimensions (L x W x H):</b>	7" x 4" x 1.75" in	6.875"x4.375"x2.25	4.67 x 7.99 x 2.3 in	6.25"x 4.38 "x 2.25" in	6" x 5.25" x 2" in
<b>Weight:</b>	2 lbs	1.2 lbs.	2.2 lbs	1.45 lbs	2 lbs
<b>Warranty:</b>	1 Year	Limited Lifetime	2 Year	2 Year	2 Year
<b>Link:</b>	<a href="#">PWRINV400R</a>	<a href="#">10-00477</a>	<a href="#">7392</a>	<a href="#">CPI-480</a>	<a href="#">PI400AB</a>
<b>Price:</b>	\$34.00	\$34.00	\$34.00	\$34.00	\$37.99



	<b>Power Bright 400</b>	<b>Vector 400</b>	<b>Whistler 400</b>	<b>Samlex 400</b>	<b>Xantrex 400</b>
<b>Manufacturer:</b>	Power Bright 400	Vector 400	Whistler 400	Samlex 400	Xantrex 400
<b>Model:</b>	PW400-12	VEC024B	PI-400W	SI-400HP	851-0400
<b>DC Input:</b>	12 Volt	12 Volt	12 Volt	12 Volt	12 Volt
<b>Continuous Power:</b>	400 Watts	400 Watts	400 Watts	400 Watts	320 Watts
<b>Surge Power:</b>	800 Watts	800 Watts	800 Watts	800 Watts	600 Watts
<b>Receptacles:</b>	2	2	2	2	2
<b>USB Port:</b>	No	No	No	No	No
<b>Bonus Port:</b>	No	No	No	No	No
<b>Cooling Fan:</b>	Yes	Yes	Yes	Yes	Thermal
<b>Enclosed Cables:</b>	Cig & Direct	Cig & Direct	Cig & Direct	Cig & Direct	Cig & Direct
<b>Operating Voltage:</b>	10 to 15 Volts	10.5 to 15 Volts	9.5 – 16 Volts	10.5 to 15.6 Volts	10 to 15 Volts
<b>Output Voltage:</b>	120 Volts AC	120 Volts AC	120 Volts AC	120 Volts AC	120 Volts AC
<b>Output Wave Form:</b>	Modified	Modified	Modified	Modified	Modified
<b>Output Frequency:</b>	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz
<b>Over Temp Protection:</b>	Yes	Yes	Yes	Yes	Yes
<b>Over Load Protection:</b>	Yes	Yes	Yes	Yes	Yes
<b>Low Voltage Alarm:</b>	10.5 +/-0.5 Volts	< 11.5 Volt DC	10.5 +/-0.5 Volts	10.6 Volts	10.7 Volts
<b>Low Voltage Shutdown:</b>	10.0+/-0.5 Volts	< 10.5 Volt DC	10.0+/-0.5 Volts	10 Volts	10 Volts
<b>No Load Current:</b>	< 0.12A	0.4 Amps	< 0.40A	< .2 A	< .2 A
<b>Full Load Efficiency:</b>	85%	85%	85%	85%	85%
<b>1/3 Load Efficiency:</b>	90%	90%	90%	90%	90%
<b>Dimensions (L x W x H):</b>	7.4" x 5" x 2" in	4.75" x 6" x 1.75"	7.35" x 5" x 3"	6.3" x 6.3" x 2.17"	5.9" x 4.1" x 2.25"
<b>Weight:</b>	2.6 lbs	2 lbs	2 lbs	2.9 lbs	1.4 lbs
<b>Warranty:</b>	1 Year	2 Year	2 Year	2 Year	1 Year
<b>Link:</b>	<a href="#">PW400-12</a>	<a href="#">VEC024B</a>	<a href="#">PI-400W</a>	<a href="#">SI-400HP</a>	<a href="#">851-0400</a>
<b>Price:</b>	\$34.99	\$34.00	\$34.99	\$44.00	\$39.99



	<b>Wagan 400</b>	<b>Power Bright 400</b>	<b>Power Bright 400</b>
<b>Manufacturer:</b>	Wagan 400	Power Bright 400	Power Bright 400
<b>Model:</b>	2003	ML400-24	ERP400-12
<b>DC Input:</b>	12 Volt	24 Volt	12 Volt
<b>Continuous Power:</b>	400 Watts	400 Watts	400 Watts
<b>Surge Power:</b>	1000 Watts	800 Watts	800 Watts
<b>Receptacles:</b>	2	2	1
<b>USB Port:</b>	No	No	No
<b>Bonus Port:</b>	No	No	No
<b>Cooling Fan:</b>	Yes	Yes	Yes
<b>Enclosed Cables:</b>	Cig & Direct	Cig & Direct	Cig & Direct
<b>Operating Voltage:</b>	10 to 15 Volts	20-30V	10 to 15 Volts
<b>Output Voltage:</b>	120 Volts AC	120 Volts AC	220 Volts AC
<b>Output Wave Form:</b>	Modified	Modified	Modified
<b>Output Frequency:</b>	60 Hz	60 Hz	50 Hz
<b>Over Temp Protection:</b>	Yes	Yes	Yes
<b>Over Load Protection:</b>	Yes	Yes	Yes
<b>Low Voltage Alarm:</b>	10.5V	21 +/- 0.5V	10.5 +/-0.5 Volts
<b>Low Voltage Shutdown:</b>	9.5 +/- 0.5 Volts	20.5 +/- 0.5V	10.0+/-0.5 Volts
<b>No Load Current:</b>	< 0.75 Amps	< 0.1A	< 0.1A
<b>Full Load Efficiency:</b>	87%	85%	85%
<b>1/3 Load Efficiency:</b>	90%	90%	90%
<b>Dimensions (L x W x H):</b>	7.5" x5" x 2"	7.4" x 5" x 2" in	7.40" x 5.0" x 2.0"
<b>Weight:</b>	2 lbs	2.6 lbs	3.0 lbs
<b>Warranty:</b>	1 Year	1 Year	1 Year
<b>Link:</b>	<a href="#">2003</a>	<a href="#">ML400-24</a>	<a href="#">ERP400-12</a>
<b>Price:</b>	\$34.00	\$39.99	\$41.00